

Company Logo		<b>DECLARATION of PERFORMANCE</b>	document reference
--------------	---	---------------------------------------	--------------------

**DOP-FL-20251023**

1- Unique identification code of the product-type:

**ACACIA FILM FACED PLYWOOD FVA**

Thicknesses: 12/15/18/20/21MM      Widths: 1250MM      Lengths: 2500MM

2- Type, batch or serial number or any other element allowing the identification of the construction product in accordance with Article 11 (4) of Regulation (EU) No 305/2011:

**See parcel number**

3- Intended use or use of the construction product in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Use of Non-Structural Components outdoor in Exterior environments**

4- Name, trade name or registered trademark and contact address of the manufacturer in accordance with Article 11 (5) of Regulation (EU) No 305/2011:

**NAME: FULIN WOOD IMPORT EXPORT COMPANY LIMITED**

**ADD: No. 64 Le Trien Street, Dinh Ke Ward, Bac Giang City,  
Bac Giang Province, Vietnam**

5- If applicable, the name and contact address of the representative in accordance with Article 12 (2) of Regulation (EU) No 305/2011:

**Not applicable**

6- System or systems for the assessment and verification of the constancy of performance of the construction product in accordance with Annex V of Regulation (UE) N°305/2011 :

**System 2+**

**0407-CPR-2228 (IG-113-2025)  
ISTITUTO GIORDANO SPA**

7- In case of the declaration of performance concerning a construction product covered by a harmonized standard :

**EN 13986 + A1 : 2015**

8- In case of the declaration of performance concerning a construction product for which a European Technical Assessment as been issued :

**Not applicable**

Company Logo		<b>DECLARATION of PERFORMANCE</b>	document reference
--------------	---	-----------------------------------	--------------------

9- Declared performances

Essential characteristics	Harmonised technical specifications	Declared performance
Density		600+ /-20KG/M3
Reaction to Fire	EN 13986	d-s2,d0
Modulus of Elasticity Flexural (N/mm2)	EN 310	” ≥4500
		⊥ ≥3000
Breaking stress Flexural (N/mm2)		” ≥40
		⊥ ≥30
Punch Shear Shear (for floors and roofs)	EN 12871	Not applicable
Bracing Strength (for walls)	EN 1995-1-1	Not applicable
Impact Resistance (for floors, roofs and walls)	EN 12871	Not applicable
Water Vapor Permeability	EN 13986 +A1 : 2015	NPD
Formaldehyde release	EN 717-2	E1
Pentachlorophenol content	EN 13986 +A1 : 2015	≤5ppm
Airborne Noise Insulation	EN 13986 +A1 : 2015	NPD
Sound absorption coefficient	EN 13986 +A1 : 2015	NPD
Thermal Conductivity	EN 13986 +A1 : 2015	NPD
Local Lift	EN 1995-1-1	NPD
Air permeability	EN 12114	NPD
Bonding Strength	EN 314-2	EN314 -2 class 2
Internal cohesion	EN 319	NPD
Swelling in thickness	EN 317	NPD
Moisture Resistance	EN 314-2	See bonding strength
Mechanical Durability	EN 1156	NPD
Biological Sustainability	EN 335-3	Class 3

10- The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

Company Logo		<b>DECLARATION of PERFORMANCE</b>	document reference
--------------	---	-----------------------------------	--------------------

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by

General Manager  
2025/10/23



**GIAM ĐỐC.**  
**DOÃN THỊ NGUYỆT**